

SRT

SEALANT RUSTPROOFING FOR TRAILERS

SRT is a SEALANT RUSTPROOFING FOR TRAILERS formulated to seal the floorboards and provide superior protection against rust and corrosion to the metal structure and mechanical parts of semi-trailers.

Once applied, the **SRT** will form a dry protective film with excellent characteristics:

- Will penetrate into cracks and seals the joints of the floorboards
- Excellent rust protection
- Superior resistance to abrasion
- Very good adherence
- Remains pliable : will not crack
- Will not drip
- Self-healing properties
- Is odorless

APPLICATION :

- **SRT** must be applied on a clean surface, free from any traces of dirt, oil or grease thus allowing optimum adherence of the product.
- **SRT** can be applied by using a brush but should be applied with a rustproofing gun or an airless pump for optimum results. Avoid the over spraying of product on the surface.
- The surface must be at a temperature of over 16°C (60°F) when applying **SRT**.

STORAGE

- Store at a temperature between -15°C (5°F).and 50°C (120°F).

TECHNICAL DATA

- Brookfield Viscosity @ 25°C, cPS : 10,000
- Flashpoint d'éclair, ASTM D93, °C : 60
- Boiling point, °C : >150
- Solubility in water : Insoluble
- Colour : Black

Sizes	Product numbers
4 L	227004
20 L	227020
55 L	227055
205 L	227205

The data provided in this document is for information purposes only. **HIPERTECH INC.**, having no control over the application and the use of this product, limits its responsibility to the quality of the product supplied.